



ISO8528

GC ;) &

SZUTEST

GC - \$\$\$

CE

2000/14/EC

&\$\$\$#(#

z* \$ z' %z\$D:

	"	"	"	"	Amp
480/277		248,00		216,00	325,00
380/220		227,00		206,00	391,00
208/120		248,00		214,00	743,00

fPGDL

=GC ;) &

,) & z

rDF DL

%\$i

%

%&

=GC " \$(**

z&(

=GC

Standard Specifications

z

fl

!

E

z

z

Manufacturer		John Deere		
Model		6081 HF		
	L	8,10		
	"	116 X 129		
		15.7:1		
	fl # Ł	"# "	1800	
	fl "Ł	L	32,00	
		L	44,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	21,20		
	' # "	58,00		
	° C	514		
		12 V d.c.		
	Load	%\$İ	'+) İ)\$İ
	# "			
		64,80	47,90	32,00

		Stamford
		UCI 274K
	Hz	60
	"	250
7 cg'		0,80
		3
	fl Ł	480/277
	A	375
Temperatur		H

		fl "Ł		fl "Ł	
	"	"	"	"	L
AJD 248-6	2150	2270	1150	1800	420
		fl "Ł		fl "Ł	
	"	"	"	"	L
AK 60	2910	3800	1210	2000	500



