



ISO8528

GC ;) &-

SZUTEST

GC - \$\$\$

CE

2000/14/EC

&\$\$\$#(#

z*\$' z'z' D:

	"	kw	"	kw	Amp
480/277		355,00		323,00	485,00
380/220		355,00		320,00	608,00
208/120		355,00		321,00	1114,00

fP GDE

GC ;) &

) & z

fDF DE

%\$1

%

%&

GC " \$(**

z&(

GC

Standard Specifications

z

fl

!

E

z

z

ALTERNATOR

D; A Z'5JF

TRANSFER SWITCH

Manufacturer		Doosan		
Model		P158LE-1		
		%	\$	#
		402,00 kw [539,00HP]		
	L	14,600		
	"	128x142		
		15:1		
	fl # ı	"#	"	1800
	fl ı	L	21,00	
		L	68,50	
AbsorbedAirDischargeReSourceKey.Text	' # "	33,70		
	' # "	73,50		
	° C	500,00		
		24 V d.c.		
	Load	%\$ı	'+)ı)\$ı
	# "	91,30	67,50	46,50

		Stamford		
		HCI444F		
	Hz	60		
	kw	400,00		
7 cg'		0,80		
		3		
	fl ı	480/277		
	A	601,00		
Temperature		H		

		fl ı		fl ı	
	"	"	"	"	L
AD 355-6	3170,00	3031,00	1550,00	1985,00	700,00
		fl ı		fl ı	
	"	"	"	"	L
MS 70	4145	4460	1606	2477	700

AD 355-6

Doosan
Stamford
D+ & "



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1606
fl "L	"	4460
fl "L	"	2477
	L	700